

1080P HDMI EXTENDER OVER IP

P2K-HRSL3E1 / P2K-LHRS1E3

P2K-HRSL3E1-P / P2K-LHRS1E3-P (PoE)



OVERVIEW

The Partilink 1080P HDMI Extender series is composed of transmitter and receiver to extend HDMI, RS-232 and IR over IP via CATx cable and Gigabite Ethernet switch. Suitable for point to point uni-cat, point to multi-point or multi-point to multi-point multi-cast.

FEATURES

- RS-232 bi-directional extension
- 4 bits switch for 16 stream channel selection
- 2 bits switch for 8 RS-232 Baud rate setting
- HDCP compliant and Blu-Ray ready
- IR extension
- Automatic EDID configuration
- Networking environment under 10/100 BASE-T switch hub and CAT-5 cable switch hub and CAT-5 cable
- Point to point extension, unicast and multicast
- Point to point extension via CATx without Ethernet switch up to 100M
- PC tool Ethernet and web UI control
- P2K-HRSL3E1-P / P2K-LHRS1E3-P version supports Power over Ethernet

APPLICATION


- Unicast, point to point extension
- Multicast, point to multi points or multi points to multi points extension
- Screen wall installation

■ Unicast




■ Multicast

a. Video Distribution



b. Matrix Distribution



SPECIFICATION

MODEL NO.	P2K-HRSL3E1 P2K-HRSL3E1-P Transmitter	P2K-LHRS1E3 P2K-LHRS1E3-P Receiver
INPUT	HDMI Type-A female connector	None
OUTPUT	HHDMI Type-A female connector for loop through	HDMI Type-A female connector
IR	3.5mm phone jack for IR emitter to control video source device	3.5mm phone jack for IR receiver cable to receive remote signal
COMPRESSION	<ul style="list-style-type: none"> • H.264 compression video format Full HD encoder/ decoder • MP3 compression audio format stereo 192Kbps encoder/ decoder. • Media stream up to 18Mbps 	
HDMI INPUT RESOLUTION	1080p 60/50, 1080p 30/25, 1080i 60/50, 720p 60/50, 480i 60/50, 480p 60/50	
HDMI OUTPUT RESOLUTION	1080p 60/50, 1080i 60/50, 720p 60/50, 480i 60/50, 480p 60/50	
AUDIO FORMAT	Stereo 192Kbps	
IP PROTOCOL	TCP, UDP, RTSP, RTP, DHCP, IGMP, Multicast, IPV4	
LAN PORT	RJ-45 connector for 10/100 BASE-T CAT-5 extension	
SERIAL	DB-9 female connector for RS-232	
POWER INPUT	<ul style="list-style-type: none"> • 2.0mm power jack for DC5V/2A • RJ-45, Power over Ethernet 36V~57V / 7W in (PoE model only) 	
OPERATING TEMPERATURE	0~55 °C	
OPERATING HUMIDITY	5%~90% RH	
POWER ADAPTER	AC in 100~240V (50~60Hz), DC5V/2A out	
	ESD protection air gap discharge $\pm 8KV$, contact discharged $\pm 4KV$	
DIMENSION	130 x 82 x 30.25 mm (L x W x H)	
WEIGHT	290 G per transmitter or receiver unit	
FRONT & BACK VIEW	